

INDEX

(Guide to Index: *i* and *t* refer to illustrations and tables respectively)

- alteration of foam, 9, 67–88
 - approach to the study, 71–75, 72*t*, 74*i*–75*i*
 - experimental results, 76–83, 76*i*, 78*i*–81*i*, 83*i*
 - lamella thickness, 77–79, 79*i*
- alteration of wettability
 - approach to the study, 15–33, 38–44, 71–75, 93–95, 108–14
 - experimental results, 22–32, 44–62, 76–82, 96–101, 114–24
 - using chemicals, 15–30
 - using nanoparticles, 35–63, 67–83, 89–101, 105–25
- ammonium hydroxide, 38–39, 38*t*–39*t*, 45
- apparent viscosity,
 - capillary viscometer, 71–75, 74*i*
 - foam, 79–82, 80*i*–81*i*,
in porous media, 27–30, 70–83, 112–25
- base fluid, 112–13, 113*t*
- base oil,
 - drilling fluids, 3–5
see also a well, 3–5, 4*i*
 - environmentally friendly, 90
 - Novasol, 3
 - Sarapar, 3
 - formation damage, 3–5, 16–18
- Berea core, 18–20, 19*i*, 57–59, 57*i*, 58*i*
- biopolymer, 8
- brine, 19–30, 56–63, 71–83, 93–101, 108–25
- butane, 2
- capillary pressure, 41–44, 59–63, 60*i*, 73

- carbon dioxide, 71–75, 74*i*
 - 75*i*,
 - injection, 9, 17, 73
- carbon nanotubes, 36
- chemical EOR, 105–06
 - see also* enhanced oil recovery
- chemical compounds
 - ammonium hydroxide, 38, 45
 - diesel, 18–30
 - ethanol, 35–37, 107
 - kerosene, 20–30
 - n-decane, 56–60, 58*i*, 60*i*
 - paraffin oil, 71–83, 98–100, 108
 - perfluorodecil-triethoxy-silane, 35–63
 - silicon dioxide, 67–83
 - sodium chloride, 71–82, 93–101, 106–24
 - sodium dodecyl sulphate, 72–83, 93–101, 112–14, 116–25, 117*i*–22*i*, 123*t*, 124*i*
 - synthetic oil, 72
 - tetraethoxysilane, 38–62
 - titanium oxide, 36–37
 - WA A, 17–30
 - WB B, 17–30
 - WC C, 17–30
 - zinc oxide, 108–25, 113*t*, 115*i*, 117*i*–22*i*
- chemical injection, *see* chemical EOR
- CMC, *see* critical micellar concentration
- condensate banking
 - removal, approach to the study, 18–21, 19*t*–20*t*, 19*i*–21*i*
 - challenges, 17–18
 - experimental results, effects of surfactants
 - on wettability, 21–30, 22*i*–24*i*, 26*i*
 - effects of wettability alteration on relative permeability, 27–30, 28*i*–29*i*
- condensate blockage
 - removal, *see* condensate banking removal
- contact angle, 21–30, 22*i*–25*i*, 41–44, 41*i*, 56–59, 76–77, 94–98, 110–11, 120–25
 - see also* Krüss DSA25E
- CO₂, *see* carbon dioxide
- core samples

- limestone, 2, 35, 90, 93–101, 96*i*
- sandstone, 2, 18–30, 20*i*, 56–59, 112–16, 120–25, 123*t*
- critical micellar
 - concentration, 107–08, 123*t*
- crude oil, 2–4, 17, 93–95
 - original oil in place, 123–25
 - see also* oil recovery
- detachment energy, 72–73
- dew point, 15–17
- diesel, 18–30
- DLS, *see* dynamic light scattering
- drilling fluids,
 - apparent viscosity, 5
 - fluid loss, 5
 - formation damage, 4–5, 15–18
 - emulsion, 5
 - mitigation, 5
 - mud filtrate, 5
 - gel strength, 5
 - nanoparticles in, 5, 7–9
 - see also* nanoparticles
 - oil-based mud,
 - base oil, 3
 - Novasol, 3
 - Sarapar, 3
 - OPEX, 5
 - plastic viscosity, 5
 - rheological properties, 5
 - water-based mud, 3
 - yield point, 5
- dry gas, 2, 6–8
 - ethane, 2
 - methane, 2
- Du Noüy method, 109–10
- dynamic light scattering, 39–40, 49, 51, 109, 114–15, 115*i*
- EDL, *see* electrical double layer
- effects of saline solution
 - with SiNPs and SDS, on IFT, 98–100, 99*i*
 - on limestone wettability, 96–98, 96*i*–97*i*
 - on zeta potential, 39, 52, 52*t*, 93–95, 100–01, 114–16, 115*i*
- electrical double layer, 93
- enhanced oil recovery, 7–9, 35–93, 67–101, 105–25
- biopolymer, 8
- carbon dioxide
 - injection, 8–9, 16–17, 67
- changes in,
 - interfacial tension, 8–9, 53–62, 99–101, 99*i*, 108–

- 11, 116–20, 118*i*–19*i*
- wettability, 8–9, 30, 35–63, 72–74, 89–101, 116–23
- chemical, 19, 38–39, 71–72, 72*t*, 94–95, 94*t*, 112–13, 113*t*
- foam,
 - nanoparticle stabilised, 69–83
- microbial, 105
- miscible gas injection, 8–9, 67, 105
- nanoparticles, 8–9, 35–63, 67–83, 89–101, 105–25
- nano-xanthan flooding, 8
- thermal, 105
- EOR, *see* enhanced oil recovery
- ethane, 2
- ethanol, 35–38, 41, 44–49, 52–56, 107
- experimental results
 - capillary tube test 41–42, 42*i*, 59–60, 60*i*
 - condensate banking removal, 21–30
 - contact angle, 21–30, 22*i*–25*i*, 41–44, 41*i*, 56–59, 76–77, 94–98, 110–11, 120–25
 - effects on IFT, 116, 118–20, 118*i*–19*i*
 - foam lamella thickness, 77–79, 79*i*
 - foam apparent viscosity, 79–82, 80*i*–81*i*
 - FTIR, 44–48, 47*i*, 63
 - imbibition test, 60–63, 62*i*
 - nanoparticles size distribution, 49–51, 50*i*, 108–09, 109*i*, 114–15, 115*i*
 - sandpack displacement, 27–30, 28*i*–29*i*, 123–25, 123*t*, 124*i*
 - SiO₂ nanoparticles functionalisation, 44–48, 46*i*–48*i*
 - stabilised foam, 79–82, 80*i*–81*i*
 - surface characterisation, 53–54, 53*i*–54*i*

- surface tension, 116, 118, 118*i*
 - TGA, *see* thermal stability
 - thermal stability, 54–56, 55*i*
 - wettability of
 - limestone, 96–99, 99*i*
 - zeta potential, 52, 52*t*, 100–01, 100*i*, 114–07, 117*i*
- studies,
 - nanoparticles in
 - EOR, 35–63, 67–83, 89–101, 105–25
 - wettability
 - alteration, 15–30, 35–63, 89–101, 105–25
- FAS17, *see*
 - perfluorodecyltriethoxysilane
- FESEM, *see* field emission scanning electron microscope
- field emission scanning
 - electron microscope, 40, 49–51, 50*i*, 50*t*, 63
- foam in EOR, 8–9, 67–83
 - approach to the study, 71–75, 72*t*, 74*i*–75*i*
 - experimental results,
 - foam apparent
 - viscosity, 79–82, 80*i*–81*i*
 - foam flooding, 82–83, 83*i*
 - foam lamella
 - thickness, 77–79, 79*i*
 - foam stability, 76–79, 66*i*
 - oil recovery, 123–25, 124*i*
 - SiO₂ nanoparticles
 - stabilised foam, 76–77, 76*i*
 - glass beads pack, 82–83, 83*i*
 - see also* foam stability
 - stabilised by
 - nanoparticles, 76–77, 76*i*
 - foam lamella thickness, 77–79, 78*i*
 - KH550-stabilised foam, 76–82, 79*i*–81*i*
 - SDS-stabilised foam, 76–83, 76*i*–81*i*
 - foam stability,
 - bubble's mean size, 77–79, 78*i*

- bubbles coalescence, 68–69
- coarsening, 68–69
- foam texture, 71–78, 78*i*
- lamella, 77–79, 79*i*
- liquid drainage, 77, 79
- see also* foam in EOR
- formation damage,
 - caused by,
 - filtrate invasion, 3, 5
 - reduced by,
 - nanoparticles, 8–9
 - see also* drilling fluids
- Fourier transform infrared, 37–39, 45–47, 47*i*, 63
- FTIR, *see* Fourier transform infrared
- gas condensate, 6–7, 15–17, 35
- gas flooding, 8, 73, 82
- gas injection, 8, 73, 105
- gel strength, 3, 5
- glass beads, 71–73, 112–13, 113*i*
 - see also* glass beads pack
- glass beads pack, 71–73, 72*t*, 82–83, 83*i*
- glass capillary tube rise test, 41–42, 59–63, 60*i*
- gravity segregation, 67
- high salinity water, 89–101, 105–25
- high shrinkage oil, 7
- HSW, *see* high salinity water
- hydrocarbon,
 - and mankind, 1–3, 2*i*
 - definition, 2–3
 - drilling fluids, 3, 5
 - oil recovery, 28–33, 30*i*–33*i*, 93–94, 93*i*, 136–38, 136*t*, 137*i*, 169–70, 169*t*, 170*i*
 - production, 1–9, 4*i*,
 - challenges, 7–9
 - definition, 2–3
 - improve, 7–9, 15–30, 67–83, 89–101, 105–25
 - reservoirs, 2–9, 4*i*, 15–31, 36, 67–68
 - traps, 5–6
 - types, 2–3, 6–9
 - black oil, 7
 - dry gas, 7
 - retrograde gas
 - condensate, 7–9, 15–30
 - volatile oil, 7–9
 - wet gas, 7–8
 - usage, 1–2, 2*i*
 - well, 3–5, 4*i*,
 - drilling fluids, 3, 4
- HC, *see* hydrocarbon

- reservoirs, 2–9, 4*i*,
15–31, 36, 67–
68
- traps, 5–6
- hydrocarbon recovery using
nanoparticles, 7–9, 35–
63, 67–83, 83*i*, 89–101,
105–25, 124*i*
- approach to the study,
38–44, 71–75, 93–
95, 108–14
- characterisation,
39–54, 46*i*–47*i*,
53*i*–54*i*
- functionalisation,
44–48, 43*i*–48*i*
- glass beads pack,
71–73, 72*t*, 82–
83, 83*i*
- sandpack, 27–30,
28*i*–29*i*, 123–25,
123*t*, 124*i*
- wettability test, 21–
26, 44–63, 96–
98, 120–23
- experimental results,
21–29, 85–93, 76–
83, 96–101, 112–24
- capillary test, 59–
60, 60*i*
- contact angle, 15–
30, 35–63, 69–
72, 76–77, 89–
97, 106–11,
120–23
- IFT, 90–91, 98–
100, 116–20,
123–24
- imbibition test, 60–
62, 62*i*
- nanosilica
functionalisation,
44–48, 45*i*–48*i*
- oil recovery, 28–33,
30*i*–33*i*, 93–94, 93*i*,
136–38, 136*t*, 137*i*,
169–70, 169*t*, 170*i*
- sandpack, 27–30,
28*i*–29*i*, 123–25,
123*t*, 124*i*
- size distribution,
49–51, 51*t*, 114–
15, 115*i*
- surface
characterisation,
53–54, 53*i*–54*i*
- thermal stability,
54–56, 55*i*
- zeta potential, 39,
52, 52*t*, 93–95,
100–01, 114–16,
115*i*
- hydrophilic, 72, 76, 89, 91
- hydrophobic, 36, 68–69,
72*t*, 82–83, 91

- IFT, *see* interfacial tension
- imbibition test
see also spontaneous
 imbibition test
- improve condensate
 recovery, 15–30
 approach to the study,
 18–21, 19*t*–20*t*, 19*i*–
 21*i*
 Krüss DSA25E, 20–
 21, 21*i*, 30, 110–
 11
 sandpack, 27–30,
 28*i*–29*i*, 123–25,
 123*t*, 124*i*
 sandstone core
 slices, 19, 19*i*
 sessile drop method,
 20–21, 72, 94,
 96, 120
 challenges, 17–18
 experimental results,
 relative permeability
 changes, 27–30,
 28*i*–29*i*
 wettability of
 sandstones, 21–
 29, 22*i*
- improved oil recovery,
 nanoparticles,
 recovery enhancer,
 7–9, 35–63, 67–
 83, 83*i*, 89–101,
 105–25
see also enhance oil
 recovery
 waterflooding, 7–9
- injection,
 carbon dioxide, 7–9, 67
 kerosene, 27–30
 methane, 67
 nitrogen, 67
 propane, 17
 water, 7–9, 82
- interfacial tension, 8–9, 53–
 62, 99–101, 99*i*, 108–
 11, 116–20, 118*i*–19*i*
- IOR, *see* improved oil
 recovery
- KH550-stabilised foam,
 76–82, 79*i*–81*i*
- Krüss DSA25E, 20–21, 21*i*,
 30, 110–11
see also contact angle
- Krüss tensiometer, 95, 108–
 10, 110*i*
see also interfacial
 tension
- limestone plate, 93–95
- liquid condensate, 7, 15
- low salinity water, 93–101,
 125–25
 IFT, 90–91, 98–100,
 116–20, 123–24
- low shrinkage oil, 6
- LSW, *see* low salinity water

- mature oilfield, 105
- methane, 2, 7, 67
- microbial EOR, 105
 - see also* enhanced oil recovery
- miscible gas injection, 105
- MISE energy, 21
 - surfactants, 17–30
 - treatment, 21–29, 22*i*–24*i*, 26*i*, 28*i*–29*i*
- mobility control, 67–68
- Mount Santubong, 112
- mud filtrate
 - causes
 - emulsion, 3, 5
 - formation damage, 3, 5
- invasion, 3, 5

- NaCl, *see* sodium chloride
- nanofluid, 8, 36, 41–43, 51, 90–92, 98, 106–25
- nano-xanthan flooding, 8
- nanoparticles, 7–9, 35–63, 67–83, 83*i*, 89–101, 105–25, 124*i*
 - carbon nanotubes, 36
 - characterisation, 39–40, 44–62, 47*i*, 49*i*, 51*t*
 - FESEM, 40, 50–51, 63 50*i*, 51*t*
 - XPS, 40, 53–54, 53*i*–54*i*
- contact angle, 21–30, 22*i*–25*i*, 41–44, 41*i*, 56–59, 76–77, 94–98, 110–11, 120–25
 - measurement, 20–21, 56–59, 57*i*–58*i*, 96–94, 120–23, 120*i*–22*i*
- fluorinated silica, 38–62
- perfluorodecyltriethoxysilane, 37–47, 38*i*
- tetraethoxysilane, 35–44
- functionalisation, 44–48, 43*i*–48*i*
 - glass capillary tube test, 41–42, 59–63, 60*i*
- hydrocarbon
 - recovery enhancer, 7–9, 35–63, 67–83, 83*i*, 89–101, 105–25, 124*i*
- lamella formation in
 - foam stabilisation, 77–79, 79*i*
- mitigate formation
 - damage, 5
- preserve shale stability, 5–6
- reduce,
 - filtrate invasion, 3, 5

- size distribution,
 - 49–51, 51*t*, 114–15, 115*i*
- DLS, *see* dynamic light scattering
- spontaneous imbibition
 - test, 36–37, 43–44, 44*i*, 60–63, 62*i*
- stabilised foam
 - approach to the study, 71–75, 72*t*, 74*t*–75*i*
- surface characterisation, 53–54, 53*i*–54*i*
- synthesised, 35–63
 - characterisation, 39–40, 44–62, 47*i*, 49*i*, 51*t*
 - in-situ
 - functionalisation method, 44–48, 46*i*–48*i*
 - Stöber process, 38, 40
- thermal stability, 40, 54–55, 55*i*
- wettability alteration, 15–30, 35–63, 89–101, 105–25
- zeta potential, 39, 52, 52*t*, 93–95, 100–1, 114–16, 115*i*
- natural gas, 6–7, 16–17, 63, 67
- NH₄OH, *see* ammonium hydroxide
- non-renewable energy, 1–2
- OBM, *see* oil-based mud
- oil-based mud
 - formation damage mitigation, 3, 5
 - Novasol, 3
 - Sarapar, 3
 - see also* base oil
 - see also* drilling fluids
- oil recovery, 28–33, 30*i*–33*i*, 93–94, 93*i*, 136–38, 136*t*, 137*i*, 169–70, 169*t*, 170*i*
- oil wet, 16, 30, 111, 123
- oleophobic, 37, 61
- OOIP, *see* original oil in place
- operating cost expenditure, 5
- OPEX, *see* operating cost expenditure
- original oil in place, 123–25, 124*i*
- paraffin oil, 72, 95, 98, 100, 108, 108*t*, 109–12
- pentane, 2
- perfluorodecyltriethoxysilane
 - 1H, 1H, 2H, 2H-, 39–41, 37–38, 46*i*

- porous media, 27–30, 70–83, 112–25
- pressure measurement, 27–29, 28*i*–29*i*
- propane injection, 17
- relative permeability, 17, 27, 30, 36–37
- renewable energy, 1
- reservoir, 2–9, 4*i*, 15–31, 36, 67–68
 - core samples, 19–20, 20*t*, 20*i*, 43
 - fluids
 - properties, 6–8
 - saturation, 6–8
 - formation damage, 5
 - gas condensate, 6–7, 15
 - interfacial tension, 8–9, 53–62, 99–101, 99*i*, 108–11, 116–20, 118*i*–19*i*
 - oil, 1–9
 - petrophysical
 - properties, 19–20, 20*t*, 20*i*, 43
 - production
 - challenges, 7–9, 17–18
 - sustainable, 15–30
 - retrograde gas
 - condensate, 6–7, 17–18
 - structure, 5–7, 9
 - traps, 5–6
 - well, 3–5, 4*i*
- retrograde gas condensate, 6–7, 17–18
- rheological properties, 5
- salinity-responsive
 - nanoparticles, 105–28
 - approach to the study, 108–14
 - equipment and procedures, 108–11, 109*i*–111*i*, 113*i*, 113*t*
 - fluid preparation, 112
 - materials, 108, 108*t*, 112–13, 113*i*, 113*t*
 - porous media, 112–14, 113*i*, 113*t*
- challenges, 106–8
- experimental results, 114–24
 - contact angle, 120–23, 120*i*–22*i*
 - interfacial tension, 116–20, 118*i*–19*i*
 - particle size
 - analysis, 114–15, 115*i*
 - sandpack
 - displacement,

- 123–25, 123*t*,
124*i*
- surface tension, 116,
118*i*
- zeta potential, 114,
117*i*
- sandpack,
 - petrophysical
 - properties, 19–20,
20*t*, 123–24
 - test, 19–20, 123–25
 - setup, 20–20, 20*i*,
112–14, 123–24,
123*t*, 124*i*
 - results, 27–30, 28*i*–
29*i*, 113–25,
123*t*, 124*i*
- SDS, *see* sodium dodecyl
sulphate
- SDS stabilised foam, 76–
83, 76*i*–81*i*
- secondary recovery, 7–9
see also waterflooding
- sessile drop method, 20–21,
72, 94–96, 120
- Krüss DSA25E, 20–21,
21*i*, 30, 110–11
- silica,
 - nanoparticles,
 - in hydrocarbon
recovery, 7–9,
35–63, 67–83,
83*i*, 89–101,
105–25, 124*i*
 - in foam EOR, 67–
88
 - in wettability
alteration, 35–
63, 89–101,
105–25
 - see also* Stöber process
- silicon dioxide
 - nanoparticles, 7–9, 35–
63, 67–83, 83*i*, 89–
101, 105–25, 124*i*
- SiO₂, *see* silicon dioxide
- sodium chloride, 71–82,
93–101, 106–24
- sodium dodecyl
 - sulphate, 72–83,
93–101, 112–14,
116–25, 117*i*–22*i*,
123*t*, 124*i*
- spontaneous imbibition test,
60–62, 62*i*
- Stöber process, 38, 40
see also nanoparticles
- surfactants, 21–30, 22*i*–24*i*,
26*i*, 38–62, 71–82, 108–
24
- TEOS, *see* tetraethoxysilane
- tertiary recovery, 7–9
see also enhanced oil
recovery
- tests
 - characterisation

- DLS 39–40, 49, 51, 109, 114–15, 115*i*
- FESEM, 40, 50–51, 63 50*i*, 51*t*
- fluorinated silica, 38–62
- FTIR, 44–48, 47*i*, 63
- XPS, 40, 53–54, 53*i*–54*i*
- contact angle
 - measurement, 21–30, 22*i*–25*i*, 41–44, 41*i*, 56–59, 76–77, 94–98, 110–11, 120–25
- Krüss DSA25E, 20–21, 21*i*, 30, 110–11
- sandstone core
 - samples, 17–19, 43
- sandstone core
 - slices, 19–26, 19*i*
- sessile drop method, 20–21, 72, 94–96, 120
- glass capillary tube rise
 - test, 41–42, 59–63, 60*i*
- sandpack, 27–30, 28*i*–29*i*, 123–25, 123*t*, 124*i*
- petrophysical
 - properties, 19–20, 20*t*, 20*i*, 43
- results, 27–29, 28*i*–29*i*, 123–24, 123*t*, 124*i*
- setup, 18–20, 20*i*, 112–14, 113*i*
- spontaneous imbibition
 - test, 60–62, 62*i*
- surface characterisation, 53–54, 53*i*–54*i*
- DLS 39–40, 49, 51, 109, 114–15, 115*i*
- FESEM, 40, 50–51, 63 50*i*, 51*t*
- tetraethoxysilane, 35–44
- TGA, *see*
 - thermogravimetric analysis
 - see also* thermal stability
- thermal EOR, 105
 - see also* enhanced oil recovery thermal stability, 54–56, 55*i*
- thermogravimetric analysis, 54–56, 55*i*
- titanium oxide, 36–37
- traps,
 - definition, 5–6
 - stratigraphic, 5–6
 - structural, 5–6

- Vinci IFT 700, 41, 41*i*, 58
 see also contact angle
- volatile oil, 6–7
- water breakthrough, 82,
- water-based mud, 3, 5
 formation damage
 mitigation, 5
 formulation, 3, 5
 see also drilling fluids
- water wet, 17, 22–24, 27,
 30, 123
- waterflooding, 8, 82, 89,
 124
 see also water
 breakthrough
- WBM, *see* water-based mud
- well, 3–9, 4*i*
 drilling fluids, 3, 5
 base oil, 3
 oil-based mud, 3, 5
 water-based mud, 3,
 5
 hydrocarbon
 production, 3–9, 4*i*
 reservoirs, 2–9, 4*i*, 15–
 31, 36, 67–68
 fluid saturation, 9
 formation damage,
 4–5, 15–18
 formation thickness,
 8–9
 limestone, 2, 35, 90,
 93–101, 96*i*
 permeability, 17,
 27, 30, 36–37
 porosity, 6, 9, 19–
 20, 71–72, 72*t*,
 123
 sandstone, 2, 18–30,
 20*i*, 56–59, 112–
 16, 120–25, 123*t*
- traps
 definition, 5,
 stratigraphic, 5–6
 structural, 5–6
- wet gas, 7–8
- wettability alteration, 15–
 30, 35–63, 89–101,
 105–25
- approach to the study,
 18–21, 18*i*–21*i*, 18*t*–
 19*t*
- condensate recovery, 15–
 33
 challenges, 17–18
- effects on,
 interfacial tension,
 8–9, 53–62, 99–
 101, 99*i*, 108–
 11, 116–20,
 118*i*–19*i*
 zeta potential, 39,
 52, 52*t*, 93–95,
 100–1, 114–16,
 115*i*

- experimental results,
 - 15–30, 35–63, 67–
 - 83, 89–101, 105–25
 - effects of surfactants
 - on, 15–30, 67–
 - 83, 89–101,
 - 105–25
 - effect on relative
 - permeability,
 - 17, 27–30, 28*i*–
 - 29*i*, 36–37
- foam flooding, 82–83,
 - 83*i*
- hydrophilic, 72, 76, 89,
 - 91
- hydrophobic, 36–37,
 - 58–72, 72*t*, 82–83,
 - 89–91
- Krüss DSA25E, 20–21,
 - 21*i*, 30, 110–11
- screening test, 36–38,
 - 41, 63
- using nanoparticles, 35–
 - 63, 67–83, 89–101,
 - 105–25
 - effect on IFT, 90–
 - 91, 98–100,
 - 116–20, 123–24
 - effect on wettability,
 - 8–9, 30, 35–63,
 - 72–74, 89–101,
 - 116–23
 - effect on zeta
 - potential, 39,
 - 52, 52*t*, 93–95,
 - 100–1, 114–16,
 - 115*i*
- experimental
 - results, 22–32,
 - 44–62, 76–82,
 - 96–101, 114–24
- experimental setup,
 - 18–21, 28–44,
 - 71–75, 71*i*–75*i*,
 - 93–95, 108–124,
 - 109*i*–11*i*
- wettability screening test,
 - 36–38, 41, 41*i*, 63
- contact angle
 - measurement, 21–
 - 30, 22*i*–25*i*, 41–44,
 - 41*i*, 56–59, 76–77,
 - 94–98, 110–11,
 - 120–25
- glass capillary tube rise
 - test, 41–42, 59–63,
 - 60*i*
- imbibition test, 60–62,
 - 62*i*
- XPS, *see* X-ray
 - photoelectron
 - spectroscopy
- X-ray photoelectron
 - spectroscopy, 40, 53–54,
 - 53*i*–54*i*
- yield point, 5

zeta potential, 39, 52, 52*t*,
93–95, 100–01, 114–16,
115*i*

Zeta-Sizer Nano ZSP, 40,
109

zinc oxide, 109–25, 113*t*,
115*i*, 117*i*–22*i*

ZnO, *see* zinc oxide