

INDEX

- amplifier, 2, 4, 7–11, 45–46, 48, 58–59, 64
- architecture, 13–17, 62, 66–67, 71, 73, 114
- backhaul, 15, 72
- bandwidth, 12–17, 35, 49–51, 63, 65–72, 89
- bidirectional, 14, 46–47, 49, 50
- channel, 63–64, 93
- communications, 4, 12, 61–62, 116
- configuration, 4, 8–11, 13, 32–36, 63, 83, 93
- electromagnetic interference, 4, 12, 114
- energy, 7–8, 23–24, 26–29, 32, 35, 38–39, 48, 65, 71, 79–80, 83
- evanescent wave, 5, 84, 97–03, 105–06
- fabrication, 34–35, 86
- fibre optic, 1–4, 97–00, 104, 118
- flood monitoring, 113–116
- frequency, 7–8, 21, 23–27, 37, 82–83, 89
- functional splits, 17, 61, 63, 65–69, 71–73
- IoT, 64, 112, 114–15, 119
- lanthanide, 8–9, 73
- latency requirement, 17, 63, 67–68, 70–71
- lead ion, 5, 77, 83
- mobile network, 62–63, 70, 117
- multiwavelength, 9, 11, 45–48, 50–58
- optical sensor, 5, 97
- optical network, 9–10, 12–13, 16, 61, 63–64
- performance, 5, 8, 15, 17, 37, 39, 49, 51, 52, 56–57, 68–73, 98, 102, 104, 120
- plasmonic, 77, 83, 90, 93
- propagation, 1–2, 63, 78–79, 83–84, 99–00
- pulse width, 37, 39

- random fibre laser, 11, 45, 48
- refractive index, 2, 77, 83, 98, 101–02, 104–06
- SOA combinations, 45–46, 49
- sensing region, 98–00, 102–03
- spectroscopic, 97, 99
- spontaneous emission, 6–8, 27–28, 48
- sensitivity, 4–5, 77, 85, 90, 97–99, 101–02, 104
- saturable absorber, 21, 23–24, 34
- transmission, 1–3, 9, 10, 12–17, 23, 27, 61, 65, 69–70, 72–73, 84, 86, 98, 103
- total internal reflection, 3–4, 78, 98
- wavelength division multiplexing 10, 14, 63, 66