INDEX

air-cooled system, 65 ambient temperature, 16 amplitude, 92 angular velocity, 98 ash, 40 atomisation, 76

backward bent duct buoy, 85 baseline fuels, 55 biodiesel, 52 bioenergy, 5 biofuel, 16, 52 biomass, 2, 16, 29 brake mean effective pressure, 67, 71 buoy, 88

carbon dioxide, 30 carbon monoxide, 30, 78 cellulose, 43 combustion, 30, 74 chamber, 80 gases, 2 radical, 59 compression-ignition, 65 convection, 21 conversion efficiency, 91 crank angle, 80 decomposition, 24, 29 diesel, 64 ethanol, 64 ethanol-methyl ester, 65 drying, 17 dual-fuel combustion, 52 electricity, 5 energy audit, 4 energy consumption, 3 energy efficiency, 1, 5 energy-efficient devices, 4

engine speed, 74 ethanol, 68 evaporation, 16 exhausted heat, 4

feasibility, 41 flame instability, 52 flame spectra, 52–53, 57 functional testing, 35

gas turbine, 51, 59

gaseous products, 39 global reaction rate, 57 green mobility, 5 greenhouse gas, 3 gross calorific value, 43 growth rate, 45

heat transfer coefficient, 18 heating rate, 34 hemicellulose, 18, 43 hydrocarbon, 76 hydrogen, 5

in-cylinder pressure, 74 intensity, 40 intermediate species, 57 lignin, 43 lignocellulosic, 16

load, 76 lump, 20 lumped capacitance approach, 20

mass equation, 22 transport, 18 yield, 24, 42, 45 methyl ester, 68 multilevel reactor, 30

nozzle, 97

orifice, 97 oscillate, 85, 95 oxygen, 76

peak combustion temperature, 74 physical appearance, 30 pneumatic energy, 97 pre-treatment, 16

radical concentrations, 57 reactor, 30, 40 renewable energy, 1, 5 residues, 2

short alkyl radical, 57 single level, 30 single-cylinder, 65 spectra intensities, 57 sunlight, 4 sustainable development goals, 1 sustainable energy, 1 swirl flame, 55

temperature distribution, 47 gradient, 18 profile, 35 profiles, 30 thermal conversion, 16 energy, 2 equilibrium, 23 power, 59 transfer, 18 torrefaction, 16, 29 transition, 6 turbulence, 57 uniformity, 40

viscosity, 76

water column, 94

waves, 94 basin, 99 energy converter, 85 group velocity, 92 incident, 92 maker, 94